



2014+ Corvette Stingray & 2015+ Corvette Z06 Diffuser Installation Instructions:

Please watch our installation video here: <https://www.youtube.com/watch?v=mfZnOVuioBg>
Or type “**Diffflow Corvette**” on YouTube.com. You can also view the video on our website *videos* page.

Instructions:

- 1) After you have your Corvette on a lift, on a jack, or on ramps, you'll need to make sure your e-brake is off. You will be attaching a bracket on the e-brake mount, so the e-brake cable needs slack. Make sure you have objects on the front and back of your tires so your Corvette doesn't roll while you are working under it since the e-brake is off.
- 2) Connect your diffuser (left and right) together in the middle with the supplied hardware.
- 3) Install front bracket onto e-brake cable mounting area by removing the 2 nuts on left and 2 nuts on right (4 total). Slide bracket in between frame and e-brake housing. Make sure the bracket lip is facing backward towards the rear of the car. Reinstall the 4 nuts and tighten down.
- 4) Install rear bracket on exhaust hanger by removing both nuts, slide the rear bracket into place and make sure the lip is facing towards the rear of the car. Re-install the 2 nuts. Do not tighten down 100% until diffuser is mounted into place, then tighten down last.
- 5) Remove all bolts/screws in the OEM valance on the left, right and center. Hold diffuser up, and take the OEM bolts/screws that you just removed and put them through the diffuser back into their original positions. These OEM Bolts will hold your diffuser up. Do not tighten 100% until diffuser is aligned properly. Use the 4 provided nuts to secure diffuser to front and rear brackets as well.
- 6) If everything is aligned and all nuts/bolts/screws are in place, tighten down everything.

Note: If you have an aftermarket exhaust, you may have to drill your bracket holes further forward or backward.

If you have any questions, please watch the video. Submit pictures to us! dtqu1z@gmail.com

----- **THE PURCHASER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF ANY AND ALL PRODUCTS PURCHASED.**

FOR OFF-ROAD USE ONLY. Purchaser solely responsible for installation and determination of the suitability of any and all products and services obtained from manufacturer and distributor, Diffflow, LLC. Purchaser understands and recognizes that off road and racing equipment provided by Diffflow, LLC are subject to varied conditions due to the manner in which they are installed and used by purchaser. Purchaser assumes all responsibility for determination of suitability of any part sold or manufactured for purchaser's application and use; and, purchaser is not relying on the skill or judgment of Diffflow, LLC regarding suitability of any product or service. Diffflow, LLC makes no warranties whatsoever, expressed or implied, oral or written to purchaser with regard its products and services. The right to make changes in design or add to or improve on product without incurring any obligations to install the same on products previously manufactured is expressly reserved by Diffflow, LLC. Buyer agrees to indemnify and hold Diffflow, LLC and its subsidiaries, successors or assigns harmless from any claim, action or demand arising out of or incident to the buyer's installation or use of products purchased from Diffflow, LLC. All of Diffflow, LLC's parts are aftermarket replacement parts. Part numbers are used for reference only. No implication is made that these parts are the original manufacturer's parts, original equipment manufactured (OEM), are from the original suppliers, or are approved by them. Before operating vehicle, always wear a seat-belt